


Site Amenities


BY SUPERIOR RECREATIONAL PRODUCTS




Model # B6PERFP

 **SUPERIOR**[®]
RECREATIONAL PRODUCTS
A **PLAYCORE** Company


HARDWARE




5/16" x 1"
Machine Bolt




3/8" x 3"
Carriage Bolt




3/8" Washer



5/16" Washer



3/8" Keepl Nut



5/16" Keepl Nut

PRODUCT SPECIFICATIONS

B6PERFP PORTABLE BENCH WITHOUT BACK

Seat: Seats shall have a 1 ½" radius edge, fabricated from a 14 ga. plate. Holes are precision punched at 5/8" diameter. 7 gauge x 1-1/2" flat bar center support and mounting bracket understructure. Electrically MIG welded.

Coating: Oven fused functionalized polyethylene copolymer-based thermoplastic. Fluidized bed coating application with superior mechanical performance, impact resistance and UV-stability.


Frame: 2-3/8" O.D. x 12 gauge pre-galvanized structural steel tubing. Tube ends are pre-galvanized steel capped. Seat mounting points are 7 gauge x 1-1/2" die stamped steel flat bar. Cross braces are 1" O.D. x 16 gauge pre-galvanized structural steel tubing. All electrically MIG welded.

Frame Coating: Electrostatic powder coated application oven cured.

Hardware: All stainless steel hardware fasteners.


Dimensions: 6' bench portable without back. Seats are 12" wide x 72" long. Seat height is 18-1/2". Total depth of bench is 22".

COMPONENTS




ITEM NO.	PartNo	DESCRIPTION	QTY
1	T-PR72-S	6' Punched Rolled Seat	1
2	P-V942P	942P Vinyl Leg	2
3	33-02-0007	5/16" SS Washer	12
4	33-02-0008	3/8" Flat Washer (SS)	2
5	33-05-0029	5/16" x 1" Machine Bolt (SS)	6
6	33-03-0012	5/16" Kep Nut (SS)	6
7	33-03-0013	3/8" Kep Nut (SS)	2
8	P-01-04-0129	26 3/4" Brace	2
9	33-06-0058	3/8" x 3" Carriage Bolt (SS)	2

STEP 1



Attach the 6' Punched Rolled Seat to the Legs using specified hardware.

STEP 2



Attach the 26-3/4" Braces to the Legs using specified hardware as shown.

OVERALL DIMENSIONS

